



## Präzisions - Kegelsenker DIN 334 A 60 Grad

Precision - Countersink DIN 334 A 60 degrees

• 5-Schneidengeometrie

• 5-cutting edges-geometry

| Kopf ø<br>Head ø | Schaft<br>Shank | mm | kleinster ø<br>smallest ø | HSS       | HSS / TIN | HSS / TIALN | HSS / Co5 | HSS / Co5 /<br>TIN | HSS / Co5 /<br>TIALN |
|------------------|-----------------|----|---------------------------|-----------|-----------|-------------|-----------|--------------------|----------------------|
| 8,0 mm           | 8 mm            | 50 | 2,5 mm                    | ⊙ 1081080 | ⊙ 3081080 | ⊙ 6081080   |           |                    |                      |
| 12,5 mm          | 8 mm            | 50 | 2,0 mm                    | ⊙ 1081125 | ⊙ 3081125 | ⊙ 6081125   |           |                    |                      |
| 16,0 mm          | 10 mm           | 60 | 3,2 mm                    | ⊙ 1081160 | ⊙ 3081160 | ⊙ 6081160   |           |                    |                      |
| 20,0 mm          | 10 mm           | 63 | 5,0 mm                    | ⊙ 1081200 | ⊙ 3081200 | ⊙ 6081200   |           |                    |                      |
| 25,0 mm          | 10 mm           | 72 | 7,0 mm                    | ⊙ 1081250 | ⊙ 3081250 | ⊙ 6081250   |           |                    |                      |

## Präzisions - Kegelsenker DIN 334 C 60 Grad

Precision - Countersink DIN 334 C 60 degrees



- 3-Schneidengeometrie
- Satz 1 / Set 1: ø 6,3; ø 8,0; ø 10,0; ø 12,5; ø 16,0; ø 20,0 mm
- Satz 2 / Set 2: ø 6,3; ø 8,0; ø 10,0; ø 12,5; ø 16,0; ø 20,0; ø 25,0 mm

- 3-cutting edges-geometry

| Kopf ø<br>Head ø                | Schaft<br>Shank | mm | kleinster ø<br>smallest ø | HSS       | HSS / TIN | HSS / TIALN | HSS / Co5 | HSS / Co5 /<br>TIN | HSS / Co5 /<br>TIALN |
|---------------------------------|-----------------|----|---------------------------|-----------|-----------|-------------|-----------|--------------------|----------------------|
| 6,3 mm                          | 5 mm            | 45 | 1,6 mm                    | ⊙ 1060063 | ⊙ 3060063 | ⊙ 6060063   |           |                    |                      |
| 8,0 mm                          | 6 mm            | 50 | 2,0 mm                    | ⊙ 1060080 | ⊙ 3060080 | ⊙ 6060080   |           |                    |                      |
| 10,0 mm                         | 6 mm            | 53 | 2,5 mm                    | ⊙ 1060100 | ⊙ 3060100 | ⊙ 6060100   |           |                    |                      |
| 12,5 mm                         | 8 mm            | 56 | 3,2 mm                    | ⊙ 1060125 | ⊙ 3060125 | ⊙ 6060125   |           |                    |                      |
| 16,0 mm                         | 10 mm           | 63 | 4,0 mm                    | ⊙ 1060160 | ⊙ 3060160 | ⊙ 6060160   |           |                    |                      |
| 20,0 mm                         | 10 mm           | 67 | 5,0 mm                    | ⊙ 1060200 | ⊙ 3060200 | ⊙ 6060200   |           |                    |                      |
| 25,0 mm                         | 10 mm           | 71 | 6,3 mm                    | ⊙ 1060250 | ⊙ 3060250 | ⊙ 6060250   |           |                    |                      |
| 30,0 mm                         | 12 mm           | 81 | 5,0 mm                    | ⊙ 1060300 | ⊙ 3060300 | ⊙ 6060300   |           |                    |                      |
| Satz 1 6-teilig ø 6,3 - 20,0 mm |                 |    |                           | ⊙ 1060002 | ⊙ 3060002 | ⊙ 6060002   |           |                    |                      |
| Satz 2 7-teilig ø 6,3 - 25,0 mm |                 |    |                           | ⊙ 1060003 | ⊙ 3060003 | ⊙ 6060003   |           |                    |                      |



## Präzisions - Kegelsenker DIN 334 D 60 Grad mit Morsekonus Precision - Countersink DIN 334 D 60 degrees with morse taper shank

### • 3-Schneidengeometrie

### • 3-cutting edges-geometry

| Kopf ø<br>Head ø | Schaft<br>Shank | mm  | kleinster ø<br>smallest ø | HSS       | HSS / TIN | HSS / TIALN | HSS / Co5 | HSS / Co5 /<br>TIN | HSS / Co5 /<br>TIALN |
|------------------|-----------------|-----|---------------------------|-----------|-----------|-------------|-----------|--------------------|----------------------|
| 40,0 mm          | MK 3            | 150 | 12,5 mm                   | ⊙ 1121400 | ⊙ 3121400 | ⊙ 6121400   |           |                    |                      |
| 50,0 mm          | MK 3            | 160 | 16,0 mm                   | ⊙ 1121500 | ⊙ 3121500 | ⊙ 6121500   |           |                    |                      |
| 63,0 mm          | MK 4            | 190 | 20,0 mm                   | ⊙ 1121630 | ⊙ 3121630 | ⊙ 6121630   |           |                    |                      |